

ELECTRONICALLY CONTROLLED PROPORTIONING VALVES



PV Series

Starts at
\$865



- ✓ Programmable Direct- or Reverse-Acting Control
- ✓ Precision Control is Achieved via a 10-Bit Converter Controlling a 200 Step per Revolution Motor
- ✓ Rugged Construction for Industrial Applications
- ✓ External Safety Override Contacts to Open/Close Valve
- ✓ NEMA 4 (IP65) Rating for Outdoor Use
- ✓ Ideal for Liquid and Gas Applications


An electronically controlled proportioning valve (ECV) will take an electrical input signal (usually 4 to 20 mA) and proportion the amount of flow through a pipe from fully closed to fully open. The OMEGA® ECV valve features programmable direct-acting or reverse-acting control. Direct-acting means that, as the current signal rises, the valve allows more flow, while reverse-acting will decrease the flow rate with an increasing current signal.

These units can also be programmed to sense a failure in the current loop and fully close/open the valve when the signal level drops below 3.5 mA. Dry-contact remote switches can be used in conjunction with the standard current signal to provide an alarm signal that fully closes/opens the valve. An internal 5 Vdc signal is used to sense the state of the external switches.




Available with brass or stainless steel body.

The rugged epoxy-coated aluminum package ensures NEMA 4X (IP66) protection for the powerful microprocessor and servo actuator. Internally, a 10-bit A/D converter is positioning a 200 step/revolution stepper motor for precise flow. The




PV14-SS, \$1070, shown smaller than actual size.

stepper motor is directly connected to the valve stem without gearing, thereby eliminating backlash (hysteresis) effects. The valve can also be manually controlled with a screwdriver.



WT = + 4-20 GN to Blue = Full Open
 BK = - 4-20 G/W to Blue = Full Close
 R = + Ex
 R/W = - Ex
 (Does not operate
 if 4-20 is reversed)



PV series valve (with cover removed).

SPECIFICATIONS

ELECTRONICS:

Power Supply: 12 Vdc @ 3 A

Inputs: 4 to 20 mA control signal (250 Ω impedance) and dual external switch contact sensing via 5 Vdc signal

Control Modes: Direct or reverse, full or split range, high or low range, fail condition open or closed

Adjustments: Zero offset ±0.5 mA

Operating Temp: 0 to 49°C (32 to 120°F)

Enclosure: NEMA 4X (IP66), epoxy-painted aluminum

Connections: ½ NPT conduit (16" 22 AWG pigtail leads)

* Caution: Using an underrated power supply will damage the unit.

ACTUATOR:

Type: DC step motor, 200 steps/rev, 4 rev travel

Resolution: 200:1 (0.5%) (4 steps increment)

Speed: 45 rpm (5 s full stroke) except ¾" valves: 18 rpm (12 s) full stroke

Torque: 57.5 in-oz (188 in-oz ¾ valve)

VALVE:

Type: In-line globe

Temp: -18 to 120°C (0 to 250°F)

Pressure: 120 psi max (70 psi on ¾" valve)

Max Flow: GPM = C_v (ΔP/SG) ½ liquids; for gases, use standard equation found on page L-27

Wetted Parts: Ethylene propylene rubber O-ring, PTFE washer and valve body (brass models have 303 SS internal trim)

COMPLETE UNIT:

Dimensions: 216 H x 185 W x 137 mm D (8.5 x 7.3 x 5.4")

½ Valve: 229 H x 185 W x 137 mm D (9 x 7.3 x 5.4")

¾ Valve: 305 H x 203 W x 191 mm D (12 x 8 x 7.5")

Weight: 3.2 kg (7 lb); ½ valve: 4.5 kg (10 lb); ¾ valve: 8.2 kg (18 lb)

U12Y100 SPECIFICATIONS:

Power Supply: 120 Vac or 240 Vac @ 50 to 60 Hz, switchable

Output: 12 Vdc unregulated @ 3 A

Connections: 2.1 m (7') power cord, 3-pin DIN connector with 1.8 m (6') 3-conductor 22 AWG, pigtail leads

Dimensions: 102 W x 152 L x 76 mm H (4 x 6 x 3")

Weight: 1.4 g (3 lb)

 **MOST POPULAR MODELS HIGHLIGHTED!**

To Order (Specify Model Number)

MODEL NO.	PRICE	VALVE SIZE mm (in)	FITTING SIZE	C _v	MAX FLOW @ 50 psi	BODY MATERIAL
PV14-B	\$865	6.35 (¼)	½ NPT	0.6	4 GPM	Brass
PV14-SS	1070	6.35 (¼)	½ NPT	0.6	4 GPM	316 SS
PV516-B	875	7.94 (⅜)	½ NPT	1.0	8 GPM	Brass
PV516-SS	1080	7.94 (⅜)	½ NPT	1.0	8 GPM	316 SS
PV38-B	890	9.53 (⅝)	½ NPT	1.7	12 GPM	Brass
PV38-SS	1095	9.53 (⅝)	½ NPT	1.7	12 GPM	316 SS
PV12-B	1065	12.70 (½)	¾ NPT	3.5	24 GPM	Brass
PV12-SS	1325	12.70 (½)	¾ NPT	3.5	24 GPM	316 SS
PV34-B	1415	19.05 (¾)	1 NPT	6.5	45 GPM	Brass
PV34-SS	1765	19.05 (¾)	1 NPT	6.5	45 GPM	316 SS
ACCESSORIES	PRICE	DESCRIPTION				
U12Y100	\$125	Unregulated power supply 12 Vdc, 3 A				
MS-1783	58	Reference Book: Bottom-Line Automation				

Comes with complete operator's manual.

Ordering Example: PV14-B, 4 GPM brass proportioning valve, U12Y100, unregulated power supply, \$865 + 125 = \$990.



UNITED STATES

www.omega.com
1-800-TC-OMEGA
Stamford, CT.

CANADA

www.omega.ca
Laval(Quebec)
1-800-TC-OMEGA

GERMANY

www.omega.de
Deckenpfronn, Germany
0800-8266342

UNITED KINGDOM

www.omega.co.uk
Manchester, England
0800-488-488

FRANCE

www.omega.fr
Guyancourt, France
088-466-342

CZECH REPUBLIC

www.omegaeng.cz
Karviná, Czech Republic
596-311-899

BENELUX

www.omega.nl
Amstelveen, NL
0800-099-33-44



More than 100,000 Products Available!

• Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Glass Bulb Thermometers, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders Relative Humidity Measurement Instruments, RTD Probes, Elements and Assemblies, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples Thermowells and Head and Well Assemblies, Transmitters, Wire

• Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

• pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

• Data Acquisition

Auto-Dialers and Alarm Monitoring Systems, Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485 and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Strain Gages, Torque Transducers, Valves

• Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters