



Zugspannzangen

Collets

Bestell-Nr.: E	Abmessung				Bohrung serienmäßig					Anwendung
	d	D	L	W	Gewinde	Form	von	bis	stgd.	
302E 0000	8	12,7	35	20	M 6,85 x 40 Gg.	rund	1,0	60,	0,1	Boley: WW-F, Weiler, RDU 260 Schaublin: SC20, TL65-TO65 Steinel: BT4, GT4, P1, P2, PG1
319E 0000 (K12-DIN6341)	12	18	60	20	Tr. 12 x 1	rund	1,0	10,0	0,5	
324E 0000	15	21,0	56	20	M 13 x 1	rund	1,0	130,	0,5	Boley: Gr.3; Schaublin: TR102 Traub: A3, A8, A15, A20, A25
330E 0000 (K16-DIN6341)	16	24	73	20	Tr. 16x1,5	rund	1,0	13,0	0,5	Overbeck zetto: 20
349E 0000	20	26,3	73	15	S 20x1,66	rund	1,0	20,0	0,5	Schaublin: TL/TO70, TL90, W20 Manurhin: PF 32B, PF 42B, PF 60B; Studer; Voumard
351E 0000 (K20-DIN6341)	20	28	84,7	20	Tr. 20x1,5	rund	1,0	20,0	0,5	Neue Magdeburger: D 31, DH 301
355E 0000	20	28	122,7	17,5	S 20x2	rund	1,0	18,0	0,5	Deckel: FP1, FP2, S1 Maho: SK250, 650, MH 500-1000
358E 0000	23	32	86,5	20	M 21,2x1	rund	1,0	20,0	0,5	Boley: Gr.4; Carstens: AS16 Weiler: LD200, MD125
359E 0000 (K23-DIN6341)	23	32	95,6	20	Tr. 23x1,5	rund	1,0	20,0	0,5	Scherer-Feinbau Reinecker: WZS
363E 0000	25	33,5	89	16	M 23x1	rund	1,0	22,0	0,5	Boley&Leinen: A4, L3, LZ 4 R Traub: A4 (Pinole)
364E 0000	25	33,7	97,6	15	S 25x15	rund	1,5	22,0	0,5	Schaublin: W25
366E 0000	28	36	106,5	18,5	Tr. 27x20	rund	1,0	25,0	0,5	Weiler: LZ300, MF260, RD260 Boehring: VDF 1
367E 0000 (K28-DIN6341)	28	38	106,7	20	Tr. 28x1,5	rund	1,0	27,0	0,5	Mondiale Celtic
385E 0000	31,75	37,5	87	10	1,245"x20	rund	1,0	27,0	0,5	Weiler: LD330, RD260, MDU38 Dubied: 517
3713E 0000	32	140	100	15	S 29,7 x 1/15"	rund	1,0	30,0	0,5	
386E 0000 (K32-DIN6341)	32	45	116	20	Tr. 32x1,5	rund	1,0	29,0	0,5	Junkers: D40 Hahn u. Kolb: Cri-Dan B
389E 0000 (K45-DIN6341)	45	60	40	20	Tr. 45x2	rund	5,0	40,0	1,0	
10 390 0000	47	60	110	20	Tr. 47x1,5	rund	5,0	42,0	1,0	